

CP-220

- High quality portable photo printer.
- Produces brilliant photo prints and stickers anytime, anywhere directly from a PictBridge~ compatible digital camera.
- Delivers convenient and high quality postcard prints in approx 85 seconds.
- Stylish and attractive design that's easy to use - no PC required.



www.canon.com.au

Specifications

Printer Type:	Full colour direct digital printer
Printing Method:	Dye sublimation thermal print method (with overcoating)
Resolution:	300 x 300 dpi
Gradation:	256 level per colour
Ink :	Dedicated cartridge (Y,M,C and overcoating material)
Paper :	Dedicated paper for Wide size, Postcard size, L size*, Card size^^, Card size (full size label and 8-label card size stickers)
Print Size:	<ul style="list-style-type: none">❑ Postcard size, borderless: 148 x 100mm❑ Postcard size, with borders: 121.9 x 91.4mm❑ L size, borderless: 119 x 89mm❑ L size, with borders: 105.3 x 79.2mm❑ Credit card size, borderless (inc. label paper): 86.0 x 54.0mm❑ Credit card size, with border (inc. label paper): 66.7 x 50mm❑ 8-label credit card size sticker: 22 x 17.3mm (per one piece)❑ Wide size, borderless (PC only): 200 x 100mm❑ Wide size, with borders (PC only): Arbitrary with software. Through PC only.
Printing Speed:	<ul style="list-style-type: none">❑ Postcard size: 85 sec❑ L size: 70 sec❑ Credit card size: 40 sec❑ 8-label card size sticker: 40 sec❑ Wide size (not available when using CP Direct): 106 sec
PictBridge Functions:	<ul style="list-style-type: none">❑ Single image print❑ Several selected images print❑ DPOF AUTPRINT images Print❑ All images index Print - All image Print❑ Cropping Print❑ Copies❑ Date Print
Feeding System:	Auto feed from paper cassette
Paper eject system:	Auto paper eject on the paper cassette
Interface :	<ul style="list-style-type: none">❑ Digital Camera: PictBridge~ and Direct print support❑USB compliant (Type A connector) (Uses the interface cable in the camera-kit❑❑ Computer: USB compliant❑Type B connector❑

Operating Environment:	5 to 40°, 20 to 80%
Power Supply:	DC 24 V with compact power adaptor CA-CP100 or battery pack (CP-330 only) NB-CP1L [^] (22.2 V)
Power Consumption:	50W or less (idle: 4W or less)
Size:	<ul style="list-style-type: none">▣ CP-220: 170.0 × 119.0 × 54.8 mm▣ CP-330: 170.0 × 123.0 × 55.0 mm
Weight:	<ul style="list-style-type: none">▣ CP-220: Approx. 820g▣ CP-330: Approx. 860g
Compatibility:	Check www.canon.com.au/directprinting and camera websites for other PictBridge compatible models.

All data based on Canon's Standard Test Method:

Subject to change without notice:

~ Please see www.canon.com.au/digitalimage for further information on Direct Printing and PictBridge. :

[^] Battery Pack standard with CP-330 model only. CP-220 will only run on AC Power.: