

## Canon CP300 card Photo Printer

### Direct Print Convenience. Anytime. Anywhere.

- Ultimate portability thanks to included battery pack for printing on the go.
- High quality portable photo printer for direct connection to Canon digital cameras.
- Produces brilliant photo prints and stickers anytime, anywhere directly from a compatible Canon digital camera.
- Stylish and attractive silver design that's easy to use - no PC required.



[www.canon.com.au](http://www.canon.com.au)

### Specifications

<b>Printer Type:</b>	Full colour direct digital printer
<b>Printing Method:</b>	Dye sublimation thermal print method (with overcoating)
<b>Resolution:</b>	300 x 300 dpi
<b>Gradation:</b>	256 level per colour
<b>Ink Tank:</b>	Dedicated cartridge (Y,M,C and overcoating material)
<b>Paper Type:</b>	Dedicated paper for Postcard size, L size*, Card size^^, Card size (full size label and 8-label card size stickers)
<b>Paper Size:</b>	Postcard size, borderless: 148 x 100mm Postcard size, with borders: 121.9 x 91.4mm L size, borderless: 119 x 89mm L size, with borders: 105.3 x 79.2mm Credit card size, borderless (inc. label paper): 86 x 54mm Credit card size, with border (inc. label paper): 66.7 x 50mm 8-label credit card size sticker: 22 x 17.3mm (per one piece)
<b>Printing Speed:</b>	Postcard size: 85 sec L size: 70sec Credit card size: 40 sec 8-label card size sticker: 40 sec
<b>Trimming :</b>	Possible by operation from compatible Canon cameras
<b>Auto Print :</b>	Possible by operation from compatible Canon cameras
<b>Feeding system:</b>	Auto feed from paper cassette
<b>Paper eject system:</b>	Auto paper eject on the paper cassette
<b>Data transfer format:</b>	USB complaint (dedicated connector)
<b>Interface:</b>	Digital Camera: Direct Print support: USB compliant (Type A connector) (Uses the interface cable in the camera-kit) Computer : USB compliant (Type B connector)
<b>Information Display:</b>	Indication: Light or flash of LED Power On: Green light On printing: Green flash Error: Red light
<b>Operating Environment:</b>	5 to 40°C, 20 to 80%
<b>Power Supply:</b>	DC 24V (with Compact Power Adaptor CA-CP100 or Battery Pack NB-CP1L (22.2 V))
<b>Power Consumption:</b>	50W or less (idle: 4 W or less)
<b>Dimensions:</b>	170(W) x 123 (D) x 55.0 (H) mm
<b>Weight:</b>	860g (excluding paper, ink and cassette.)
<b>Compatibility:</b>	Canon PowerShot A10, A20, A100, A200, A300, A30, A40, IXUS V, IXUS V2, IXUS V3, IXUS 300, IXUS 330, IXUS 400, IXUS II, S30, S40, S45, S50, G2, G3, G5, EOS 10D, MVX2i, MVX150i. As of June, 2003. Internet firmware download may be required for IXUS 300, S30, S40 and G2