

## Canon CP330 card Photo Printer

### Direct Print Convenience. Anytime. Anywhere.

- High quality portable photo printer.
- Produces brilliant photo prints and stickers anytime, anywhere directly from a PictBridge~ compatible digital camera.
- Delivers convenient and high quality postcard prints in approx 85 seconds.
- Stylish and attractive design that's easy to use - no PC required.



[www.canon.com.au](http://www.canon.com.au)

### Specifications

<b>Printer Type:</b>	Full colour direct digital printer
<b>Printing Method:</b>	Dye sublimation thermal print method (with overcoating)
<b>Resolution:</b>	300 x 300 dpi
<b>Gradation:</b>	256 level per colour
<b>Ink :</b>	Dedicated cartridge (Y,M,C and overcoating material)
<b>Paper :</b>	Dedicated paper for Wide size, Postcard size, L size*, Card size^^, Card size (full size label and 8-label card size stickers)
<b>Print Size:</b>	Postcard size, borderless: 148 x 100mm Postcard size, with borders: 121.9 x 91.4mm L size, borderless: 119 x 89mm L size, with borders: 105.3 x 79.2mm Credit card size, borderless (inc. label paper): 86.0 x 54.0mm Credit card size, with border (inc. label paper): 66.7 x 50mm 8-label credit card size sticker: 22 x 17.3mm (per one piece) Wide size, borderless (PC only): 200 x 100mm Wide size, with borders (PC only): Arbitrary with software. Through PC only.
<b>Printing Speed:</b>	Postcard size: 85 sec L size: 70 sec Credit card size: 40 sec 8-label card size sticker: 40 sec Wide size (not available when using CP Direct): 106 sec
<b>PictBridge Functions:</b>	Single image print Several selected images print DPOF AUTPRINT images Print All images index Print - All image Print Cropping Print Copies Date Print
<b>Feeding System:</b>	Auto feed from paper cassette
<b>Paper eject system:</b>	Auto paper eject on the paper cassette
<b>Interface :</b>	Digital Camera: PictBridge~ and Direct print support <input type="checkbox"/> USB compliant (Type A connector ) (Uses the interface cable in the camera-kit <input type="checkbox"/> Computer: USB compliant <input type="checkbox"/> Type B connector <input type="checkbox"/>

**Operating Environment:** 5 to 40°, 20 to 80%  
**Power Supply:** DC 24 V □ with compact power adaptor CA-CP100 or battery pack (CP-330 only) NB-CP1L^ (2.2.2 V)  
**Power Consumption:** 50W or less (idle: 4W or less)

**Size:** CP-220: 170.0 × 119.0 × 54.8 mm  
CP-330: 170.0 × 123.0 × 55.0 mm  
**Weight:** CP-220: Approx. 820g  
CP-330: Approx. 860g  
**Compatibility:** Check [www.canon.com.au/directprinting](http://www.canon.com.au/directprinting) and camera websites for other PictBridge compatible models.

All data based on Canon's Standard Test Method:

Subject to change without notice:

~ Please see [www.canon.com.au/digitalimage](http://www.canon.com.au/digitalimage) for further information on Direct Printing and PictBridge. :

^ Battery Pack standard with CP-330 model only. CP-220 will only run on AC Power.: