



Fax EB10



Technical Specifications

Applicable line:	Public Switched Telephone Network
Compatibility:	G3
Transmission Time:	G3 ECM MMR approx. 6 seconds (Based on the Canon Fax Standard Chart No. 1)
Modem Speed:	(Tx) 14400 / 9600 / 7200 / 4800 / 2400 bps Automatic fallback
Fax Memory:	Up to 50 pages (Based on Canon Fax Standard Chart No. 1)
Automatic Document Feeder (ADF):	20 pages - Letter 10 pages - Legal
Fax Resolution:	Super fine, Fine, Standard
Toner Save Mode:	Yes
Dual Access:	Yes
UHQ™ (Ultra High Quality Image Enhancement):	64 shades of grey; Edge Enhancement
Printing Method:	Bubble Jet on demand
Printing Resolution:	360 x 360 dpi
Paper Tray Capacity (Max.):	100 sheet - Letter / Legal / A4 (approx.)
Paper Weights:	74 to 90 gsm (approx.) with automatic feed
Ink Cartridge:	Canon BX-20 Cartridge (black)
Dialling:	One-touch: 8 locations; Coded speed-dialling: 100 locations; On-hook dialling; Automatic/manual redialling; Group dialling to 107 locations
Non-ring Reception:	Receive a fax without ringing
FAX/TEL features:	Auto FAX/TEL switch; Answering machine hook-up
Other Features:	Delayed Transmission; Sequential Broadcast - up to 109 locations; Telstra FaxStream® Duet Compatible
Report / Reference:	Activity report (up to 20 transactions); Non-delivery report; TTI (Transmitter Terminal Identification); Error Tx report
Copier:	
Multiple Copy:	Up to 99 copies at the touch of a button
Other:	
Power Source:	Australia 200 - 240 V - 50 - 60 Hz
Power Consumption:	Operation: Approx. 17 W (47 W maximum) ; Approx. 9 W (standby)
Dimension (w x d x h):	427 mm x 387 mm x 193 mm (trays closed position)
Weight:	Approx 5.8 kg
Environmental:	Conditions Temperature: 10°C - 32.5°C Humidity: 20%-80% RH
In the Box:	FAX-EB10, BX-20 black ink cartridge, handset, telephone line, instruction manual, power cord, 3 year warranty card