

Canon PIXMA iP5200

- 1 picolitre FINE (Full-photolithography Inkjet Nozzle Engineering) print-head technology
- [ChromaLife 100](#) ink for beautiful, long-lasting photos
- Up to 9600 x 2400 dpi printing resolution
- ContrastPLUS 5 individual ink tank system with photo black for improved image contrast
- Prints true borderless photos up to A4 size
- Print a borderless 6" x 4" photo in approximately 36 seconds
- PictBridge and Bubble Jet Direct compatible - direct digital camera printing
- Prints directly onto printable surface CD and DVDs
- Built-in automatic duplex unit for convenient double sided printing
- Features dual paper path - auto sheet feeder (ASF) & front cassette - perfect for easy switching between plain and photo paper. Also allows huge plain paper capacity up to 300 sheets



www.canon.com.au

Specifications

Printing Method: Bubble Jet ink-on-demand with advanced FINE (Full-photolithography Inkjet Nozzle Engineering) technology

Paper Feeding: Automatic feed

Paper Type & Capacity:

- ▣ Plain Paper (13mm): 300
- ▣ Super White Paper (SW-201): 200
- ▣ High Resolution Paper (HR-101N): 160
- ▣ Photo Paper Pro (PR-101): A4: 20, 6"x4": 40
- ▣ Photo Paper Plus Glossy (PP-101): A4/5"x7": 20, 6"x4": 40
- ▣ Photo Paper Plus Semi-gloss (SG-101): A4: 20, 6"x4": 40
- ▣ Glossy Photo Paper (GP-401): A4/Credit card: 20, 6"x4": 40
- ▣ Glossy Photo Paper - everyday use (GP-501): A4: 20, 6"x4": 40
- ▣ Matte Photo Paper (MP-101): A4: 20, 6"x4": 40
- ▣ Photo Paper Plus Double sided (PP-101D): A4/5"x7": 20
- ▣ Photo Stickers (PS-101): 1 sheet
- ▣ Envelopes (DL, Com#10): 15
- ▣ Transparencies (CF-102): 60
- ▣ T-Shirt Transfers (TR-301): 2 sheets

Paper Size: A4, A5, B5, Letter, Legal, Envelopes (DL, Com. #10), 5" x 7", 6" x 4", Credit card (54mm x 86mm)

Paper Weight: Plain Paper: 64-105g/m², Canon specialty paper (max paper weight): approx 273g/m² (Photo Paper Plus Double Sided)

Print Speed: ▣ Monochrome: approx. 30 ppm

▣ Colour graphics: approx. 24 ppm

▣ Photo Paper Plus Glossy (6"x 4" image on PP-101 in standard mode): approx. 36 secs borderless

Resolution: 9600 x 2400 dpi max

Recommended ▣ Bordered printing - Top Margin: 3mm, Bottom Margin: 5mm, Left/Right margin: 3.4mm

Printable Area: ▣ Borderless photo printing - Top/Bottom/Right/Left margin: 0mm

Interface: ▣ PC: USB 2.0 Hi-Speed

▣ Camera Direct: Direct Print Port (PictBridge / Bubble Jet Direct)



Ink Tanks: □ PGI-5Bk - black ink tank
□ CLI-8C/M/Y/Bk- individual ink tanks

Ink Yield*: Borderless 6" x 4" photo: CLI-8C - approx. 390, CLI-8M - approx. 250, CLI-8Y - approx. 280, CLI-8Bk - approx. 1100

Compatibility: □ USB: Windows XP/2000/Me/98
□ Mac OS X v 10.2.1 or later

Dimensions (W x D x H): 444 x 309 x 160 mm (minimum dimensions with paper trays and other extensions)
closed)

Weight: Approx. 7.3 kg

Power Source: AC 220-240V, 50/60Hz

Power □ Max: 17W (printing)

Consumption: □ Standby: 0.8W

Acoustic Noise Level: 34.7dB(A) in best quality mode

Operating □ Temperature: 5-35°C

Environment: □ Humidity: 10-90% RH (no condensation)

Bundled Software: □ Windows: Easy-PhotoPrint, Easy-WebPrint, PhotoRecord, CD-LabelPrint
□ Macintosh: Easy-PhotoPrint, CD-LabelPrint

Included in the Box: PIXMA iP5200 Bubble Jet printer, CD Tray, Setup Software & User's Guide CD-ROM,

Printed Manual, 5 individual ink tanks (PGI-5Bk, CLI-8C, CLI-8M, CLI-8Y, CLI-8Bk),
Print-head, 12 months warranty card, Power cord, Sample Photo Paper

* Ink yield calculation is based on printing Canon 24 standard digital images on Photo Paper Plus Glossy (6" x 4" borderless print) with default settings in Windows XP driver. The figure above is an average value, measured when printing continuously using the ink immediately after it is unsealed, until the ink is out. Ink yield may vary depending on photos printed, applications software used, print mode and type of paper used. This should be used as a guide only and does not take into account ink that might be used for head cleaning or head refreshing to maintain printer performance:

Subject to change without notice. For a complete set of specifications and conditions, please refer to product brochure: