

Canon iP69600D PIXMA Bubble-Jet Printer

- Print your photos directly from compatible digital cameras, memory cards or mobile phones
- Features a huge 3.5 inch colour LCD screen for viewing images stored on your memory card
- Ultra-sharp 1 picolitre FINE technology results in enhanced shading and precise detail for superb images
- [ChromaLife 100](#) ink for beautiful, long lasting photos
- Produce high-definition photos & documents at up to 9600 x 2400 dpi
- Features a 6-colour individual ink system
- Print a borderless 6" x 4" photo in approximately 46 seconds
- Prints directly onto printable surface CDs and DVDs
- Built-in automatic duplex unit for convenient double sided printing



www.canon.com.au

Specifications

Printing Method: Bubble Jet ink-on-demand with advanced FINE (Full-photolithography Inkjet Nozzle Engineering) technology

Paper Feeding: Automatic feed

Paper Type & Capacity: □ Plain Paper (13mm): 300

□ Super White Paper (SW-201): 200

□ High Resolution Paper (HR-101N): 160

□ Photo Paper Pro (PR-101): A4: 20, 6"x4": 40

□ Photo Paper Plus Glossy (PP-101): A4/5"x7": 20, 6"x4": 40

□ Photo Paper Plus Semi-gloss (SG-101): A4: 20, 6"x4": 40

□ Glossy Photo Paper (GP-401): A4/Credit card: 20, 6"x4": 40

□ Glossy Photo Paper - everyday use (GP-501): A4: 20, 6"x4": 40

□ Matte Photo Paper (MP-101): A4: 20, 6"x4": 40

□ Photo Paper Plus Double sided (PP-101D): A4/5"x7": 20

□ Photo Stickers (PS-101): 1 sheet

□ Envelopes (DL, Com#10): 15

□ Transparencies (CF-102): 60

□ T-Shirt Transfers (TR-301): 2 sheets

Paper Size: A4, A5, B5, Letter, Legal, Envelopes (DL, Com. #10), 5" x 7", 6" x 4", Credit card (54mm x 86mm)

Paper Weight: Plain Paper: 64-105g/m², Canon specialty paper (max paper weight): approx 273g/m² (Photo Paper Plus Double Sided)

Print Speed: □ Monochrome: approx. 18 ppm

□ Colour graphics: approx. 17 ppm

□ Photo Paper Plus Glossy (6"x 4" image on PP-101 in standard mode): approx. 46 secs borderless



Resolution: 9600 x 2400 dpi max

Recommended Printable Area: Bordered printing - Top Margin: 3mm, Bottom Margin: 5mm, Left/Right margin: 3.4mm
 Borderless photo printing - Top/Bottom/Right/Left margin: 0mm

Interface: PC: USB 2.0 Hi-Speed, Bluetooth printing with optional BU-20 adaptor and Bluetooth enabled computer
 Camera Direct: Direct Print Port (PictBridge / Bubble Jet Direct)
 Mobile Phone: IrDA 1.2 (JPEG only), Bluetooth Ver. 1.2 with optional BU-20 adaptor (JPEG only)

Ink Tanks: CLI-8C/M/Y/Bk/PC/PM - individual ink tanks

Ink Yield*: Borderless 6" x 4" photo: CLI-8C - approx. 1000, CLI-8M - approx. 670, CLI-8Y - approx. 320, CLI-8Bk - approx. 1500, CLI-8PC - approx. 200, CLI-8PM - approx. 140

Compatibility: Windows XP/2000/Me/98
 Mac OS X v 10.2.1 or later

Dimensions (W x D x H): 429 x 304 x 183 mm (minimum dimensions with paper trays and other extensions closed)

Weight: Approx. 7.2 kg

Power Source: AC 100-240V, 50/60Hz

Power Max: 17W (printing)

Consumption: Standby: 2W

Acoustic Noise Level: 35dB(A) in best quality mode

Operating Temperature: 5-35°C

Environment: Humidity: 10-90% RH (no condensation)

Bundled Software: Windows: Easy-PhotoPrint, Easy-WebPrint, PhotoRecord, CD-LabelPrint
 Macintosh: Easy-PhotoPrint, CD-LabelPrint

Included in the Box: PIXMA iP6600D Bubble Jet printer, CD Tray, Setup Software & User's Guide CD-ROM, Printed Manual, 6 individual ink tanks (CLI-8C, CLI-8M, CLI-8Y, CLI-8Bk, CLI-8PC, CLI-8PM), Print-head, 12 months warranty card, Power cord, Sample Photo Paper

* Ink yield calculation is based on printing Canon 24 standard digital images on Photo Paper Plus Glossy (6" x 4" borderless print) with default settings in Windows XP driver. The figure above is an average value, measured when printing continuously using the ink immediately after it is unsealed, until the ink is out. Ink yield may vary depending on photos printed, applications software used, print mode and type of paper used. This should be used as a guide only and does not take into account ink that might be used for head cleaning or head refreshing to maintain printer performance:

Subject to change without notice. For a complete set of specifications and conditions, please refer to product brochure: