

Canon Pixma iP8500 Bubble Jet Printer

- 2 picolitre FINE (Full-photolithography Inkjet Nozzle Engineering) Technology
- ChromaPLUS 8-colour individual ink tank system with red & green
- PictBridge and Bubble Jet Direct compatible - digital camera printer
- Up to 4800 x 2400 dpi printing resolution
- Print a borderless 6" x 4" photo in around 21 seconds
- Fast print speed of up to 17ppm in black and 15 ppm in colour
- Compatible with "Digital Photo Professional"
- Prints directly onto printable surface CD and DVD
- Built-in automatic duplex unit for convenient double sided printing
- Features dual paper path - auto sheet feeder (ASF) & front cassette



www.canon.com.au

Specifications

Printing Method:	Bubble Jet ink-on-demand with advanced FINE (Full-photolithography Inkjet Nozzle Engineering) technology Automatic feed
Paper Feeding:	
Paper Type & Capacity:	Plain Paper (13mm): 300 Super White Paper (SW-201): 200 High Resolution Paper (HR-101N): 160 Photo Paper Pro (PR-101): A4: 20, 6"x4": 40 Photo Paper Plus Glossy (PP-101): A4/5"x7": 20, 6"x4": 40 Photo Paper Plus Semi-gloss (SG-101): A4: 20, 6"x4": 40 Glossy Photo Paper (GP-401): A4/Credit card: 20, 6"x4": 40 Matte Photo Paper (MP-101): A4: 20 Photo Paper Plus Double sided (PP-101D): A4/5"x7": 20 Photo Stickers (PS-101): 1 sheet Envelopes (DL, Com#10): 15 Transparencies (CF-102): 60 T-Shirt Transfers (TR-301): 2 sheets
Paper Size:	A4, A5, B5, Letter, Legal, Envelopes (DL, Com#10), 5"x7", 6"x4", Credit card (2.1" x 3.4")
Paper Weight:	64-105g/m ² (supports Photo Paper Plus Double sided PP-101D 273g/m ²)
Print Speed:	Monochrome: approx. 17 ppm Colour graphics: approx. 15 ppm Glossy Photo Print (8"x 10" image on PP-101 Draft): approx. 1.73ppm Photo Paper Plus Glossy (6"x 4"): approx. 21 seconds borderless
Resolution:	4800 x 2400 dpi max



**Recommended
Printable Area:**

Top Margin:3mm/ Bottom Margin: 5mm /Horizontal max: 203 mm

Borderless photo printing : Top and Bottom margin : 0mm /Horizontal max: up to 216mm

Interface:

USB 2.0 Hi-Speed, USB (B port), Direct Print Port (PictBridge/ Bubble Jet Direct)

Ink Tanks:

BCI-6G/R/PM/PC/C/M/Y/Bk- individual Colour ink tanks

Ink Yield:

Black: Approx. 740 pages* / Approx 1100 pages**

Colour: Cyan: Approx.1100/ Magenta: Approx.790/ Yellow: Approx.540/ Photo Cyan: Approx.380/ Photo Magenta: Approx.280/ Red: Approx.2300/ Green: Approx.2300 pages**

Compatibility:

USB: Windows XP/2000/Me/98

Mac OS 9.x, Mac OS X v 10.2.x

USB 2.0 Hi-Speed: Windows 2000/XP, Mac OS X v10.2.7 or later

Dimensions (W x D x H):

453 x 293 x 170 mm (minimum dimensions with paper trays and other extensions closed)

Weight:

Approx. 7.3 kg

Power Source:

AC 220-240V, 50/60Hz

Power Consumption:

Max: 23W (printing)

Standby: 1W

Acoustic Noise Level:

35dB(A) in best quality mode

Operating Environment:

Temperature: 5-35°C

Humidity: 10-90% RH (no condensation)

*:

Black text: 1500 characters per page, normal text, at default and plain paper mode with Windows XP using Word 2003

**:

Colour: based on printing ISO/JIS-SCID no. 5 pattern at default and plain paper mode with Windows XP using Photoshop 7.0

mtd products

mtd products

Multie Technology Distribution *mtd.* 

MTD (Multie Technology Distribution)
Phone: 1300 369 985 Fax: 1300 369 890 email: sales@mtd.net.au
www.mtd.net.au